

LOGAN



MULTIDECK Open Series

LOGAN



High Efficiency

Higher Evap. Temp $\geq -6^{\circ}\text{C}$



Standard Power

Reliable electrical integration



Optimal Cooling

Stable temperature



Smart Control

Digital Controller



Climate Type

25°C - 60% RH



More Capacity

+ 25% Storage

+ 10% Display



Energy Efficient

Lower operating cost



Tropical Ready

High Temp & Humidity



TEMPERATURE RANGE

-1 ~ 7°C

-1 ~ 5°C

4 ~ 12°C

WIDTH (mm)

1250 - 3750

HEIGHT (mm)

2000

2270

DEPTH (mm)

855

1055

POWER

220 V / 60 HZ

EFFICIENCY

GRADE 2

TEMP GRADE

M2

M1

S



LOGAN A/L SERIES GLASS DOOR MULTIDECKS

STANDARD MODEL	SHELF DEPTH 500 / 600					SHELF DEPTH 400 / 450				
	12	18	21	25	37	12	18	21	25	37
Width (mm)	1250	1880	2100	2500	3750	1250	1880	2100	2500	3750
Depth (mm)	1055					855				
Height (mm)	2000									
Op. Temperature (°C)	-1~7 / -1~5									
Temperature Grade	3 M2 / 3 M1									
Rated Voltage (V)	220V									
Rated Frequency (Hz)	60Hz									
Net Weight (kg)	245	340	375	440	645	230	300	320	410	600
Display Area (m²)	2,5	3,75	4,2	5	7,5	2,37	3,23	3,56	4,75	7,12
Effective Volume (m³)	1,14	1,71	1,91	2,28	3,42	0,89	1,21	1,34	1,78	2,68
Energy Efficiency	Grade 2									

STANDARD MODEL	SHELF DEPTH 500 / 600				SHELF DEPTH 400 / 450			
	9EA	9IA	9EL	9IL	9EA	9IA	9EL	9IL
Width (mm)	1380		1580		1380			
Depth (mm)	1055				855			
Height (mm)	2000		2270		2000		2270	
Op. Temperature (°C)	4~12							
Temperature Grade	3 S							
Rated Voltage (V)	220V							
Rated Frequency (Hz)	60Hz							
Net Weight (kg)	250	380	310	430	240	230	290	255
Display Area (m²)	3,08	1,96	3,46	2,22	2,84	2,18	3,12	2,44
Effective Volume (m³)	0,92	0,88	1,14	1,13	0,96	0,82	1,16	0,96
Energy Efficiency	Grade 2							

NOMENCLATURE

LOGAN						
L	4	D	25	A	5	R
DEPTH (mm)	SHELVES	CATEGORY	LENGTH	HEIGHT	REFRIGERANT	MODULE
E = 855 L = 1055	2 3 4 5 6	D = All M = Meat	12 = 1250 17 = 1700 18 = 1875 21 = 2100 25 = 2500 37 = 3750 9E = 90° Ext 9I = 90° Int	A = 2000 L = 2270	1 = Co2 2 = R290 3 = Glycol 4 = R454C 5 = R449A 6 = HFC (R404/R507)	R = Remote P = Plug in SP = Semi Plug in

