

LOGAN WC



MULTIDECK Warehouse Club

LOGAN WC



High Efficiency

Higher Evap. Temp $\geq -5^{\circ}\text{C}$



Standard Power

Reliable electrical integration



Optimal Cooling

Stable temperature



Smart Control

Mechanic Controller



Climate Type

25°C 60% RH



Capacity

$6.41\text{ m}^2 \cdot 3462\text{ L}$



Energy Efficient

Lower operating cost



Tropical Ready

High Temp & Humidity



TEMPERATURE RANGE

$-1 \sim 7^{\circ}\text{C}$

WIDTH (mm)

3750

HEIGHT (mm)

2050

DEPTH (mm)

1050

POWER

220 V / 60 HZ

REFRIGERANT

R404A

APPLICATION

Beverages
Dairy



LOGAN WC

Cabinet type	Open multideck (air curtain)	
Application	Beverages, dairy products	
Temperature range (°C)	-1~7°C	
Refrigerant	R404A	
Evaporating temperature (°C)	-5°C	
Cooling capacity (kW)	5.08	6.40
Ambient conditions	25°C 60%	27°C 70%
Power supply	220V 50Hz	
Defrost heater (W/A)	/	/
Anti-condensation heater (W/A)	60	0.27
Fan motor (W/A)	180	0.82
Lighting (W/A)	240	1.09
Pipe diameter	Liquid 3/8" Suction 3/4"	
Controller	HK-90W	
Expansion valve	Thermostatic expansion valve	
External dimensions (mm)	3750×1050×2050	
Packaging dimensions (mm)	3930×1166×2225	
Insulation	Rigid polyurethane foam	
Display area (m²)	6.41	
Net volume (L)	3462	
Opening width (mm)	1491	
Shelf dimensions (mm) × No. of levels	500×4	
Kick plate width (mm)	780	
Net weight (kg)	513	
Gross weight (kg)	618.2	
Drain pipe diameter	Ø50	
Standard accessories	Rubber drain trap	
Optional accessories	Glass, solid with mirror, solid side panel	

NOMENCLATURE

LOGAN						
L	4	D	25	A	5	R
DEPTH (mm)	SHELVES	CATEGORY	LENGTH	HEIGHT	REFRIGERANT	MODULE
E = 855 L = 1055	2 3 4 5 6	D = All M = Meat	12 = 1250 17 = 1700 18 = 1875 21 = 2100 25 = 2500 37 = 3750 9E = 90° Ext 9I = 90° Int	A = 2000 L = 2270	1 = Co2 2 = R290 3 = Glycol 4 = R454C 5 = R449A 6 = HFC (R404/R507)	R = Remote P = Plug in SP = Semi Plug in

