

SHASTA



PLUG-IN MULTIDECK CASE

SHASTA



High Efficiency

Higher Evap. Temp $\geq -18^{\circ}\text{C}$



Standard Power

220V Reliable operation



Temperature Range

Chiller & Freezer



Smart Control

Digital controller



Climate Type

25°C / 60% RH



Flexible Access

Sliding door / End case



Energy Efficient

Lower operating cost



Tropical Ready

High Temp & Humidity



TEMPERATURE RANGE

$\leq -18^{\circ}\text{C}$
 $+3 \sim +5^{\circ}\text{C}$

WIDTH (mm)

1455 – 2505

HEIGHT (mm)

885

DEPTH (mm)

865

POWER

220 V / 60 HZ

CONFIGURATION

Left-Right
Sliding Door
Left-Right
End Case

REFRIGERANT

R404a / R290



INTEGRAL CHEST FREEZER

STANDARD MODEL	Left-Right End Case	Left-Right Sliding Door			
	SHASTA L 18 W 2 A	SHASTA L 14 W 2 A	SHASTA L 18 W 2 A	SHASTA L 21 W 2 A	SHASTA L 25 W 2 A
Length	1.8m End case	1.5m	1.8m	2.1m	2.5m
Cabinet Dim L×W×H (mm)	1825 × 865 × 885	1455 × 865 × 885	1805 × 865 × 885	2105 × 865 × 885	2505 × 865 × 885
Package Dim L×W×H (mm)	1870×950×995	1520×950×995	1870×950×995	2170×950×995	2570×950×995
3 Level Height (mm)	2575	2575	2575	2575	2575
Effective Volume (L)	610	490	610	735	900
Gross Volume (L)	630	510	630	755	920
Gross Weight (kg)	146	129	146	160	190
Net Weight (kg)	126	111	126	140	156
Voltage (V)	220V				
Temp. Range (°C)	≤-18 / +3~+5				
Refrigerant	R404a/R290				

SHASTA				
L	18	W	2	A
COMPRESSOR	LENGTH	DEPTH (mm)	REFRIGERANT	MODULE
F = Fix L = Inverter	14 = 1455 18 = 1825 21 = 2105 25 = 2505	W = 865 U = 923	1 = R404 2 = R290	A = Left to Right B = Up and Down

