

LIBERTY



PLUG-IN MULTIDECK CASE

LIBERTY



High Efficiency
Inverter Compressor
SCE21MNX



Standard Power
Reliable electrical
integration



Temperature Range
2~8°C



Smart Control
Dixell Digital Controller



Climate Type
25°C 60% RH



Adjustable Shelving
2-Level Height/Angle Shelves



Energy Efficient
Off-Cycle Defrost System



Tropical Ready
High Temp & Humidity



TEMPERATURE
RANGE

2 ~ 8°C

WIDTH
(mm)

1250 – 2500

HEIGHT
(mm)

1500

DEPTH
(mm)

902

POWER

220~240V
60Hz

APPLICATION

Plug-in Semi
Multideck

REFRIGERANT

R290



KAIJIE PLUG IN SEMI MULTIDECK CASE

STANDARD MODEL	Liberty A 2 MT 12 L 2 P	Liberty A 2 MT 18 L 2 P	Liberty A 2 MT 25 L 2 P
Type	Plug in Semi Multideck Case		
External Dimensions (mm)	1250×902×1500	1875×902×1500	2500×902×1500
End Panel	Mirror and Glass End Panel, 40mm thickness		
Temperature Range (°C)	2~8 (25°C, 60%RH)		
Effective Volume (L)	350	520	700
Display Area (m²)	1.5	1.92	2.35
Front Height (mm)	600		
Inside Shelf	2 levels of height/angle shelves with LED (300/450mm depth)		
Shelf Qty	2×1	2×2	2×2
Night Curtain	1 L1230	2 L910	2 L1230
Compressor	SCE21MNX×1	SC15MNX×2	SCE21MNX×2
Refrigerant	R290		
Evaporators	Copper pipe with aluminum fins		
Condenser			
Type of Expaton	Capillary Tube		
Temperature Control	Dixell Digital Controller		
Defrost	Off-Cycle Defrost	Off-Cycle Defrost	Off-Cycle Defrost
Evap. Temp (°C)	-10	-10	-10
Supply Voltage	220V~240V / 50Hz	220V~240V / 50Hz	220V~240V / 50Hz
LED Lamp (W)	17W×4	12W×8	17W×8
Evaporating Fan	YZF8219×1	YZF8219×2	YZF8219×3
Anti Sweat (W)	35	52	69
PTC Heater for Evaporation Drainage (W)	500×2	500×3	500×3
Rated Current (A)	9.6	16.5	17
Input Power (W)	1950	3040	3400

NOMENCLATURE

LIBERTY						
A	1	MT	12	L	2	P
DEPTH (mm)	SHELVES	CATEGORY	LENGTH	HEIGHT	REFRIGERANT	MODULE
A = 902	1 2	MT	12 = 1250 18 = 1875 25 = 2500	L = 1500	2 = R290	P = Plug in

